



# Technical Data

**ROCOL®**

## Performance you can trust

Flexibility (Conical Mandrel ASTM D522/ISO 6860)	Excellent
Solvent Resistance: (After 7 Days)	Resistant to most general chemicals for example: Detergents, Petrol, Diesel and Oil
Resin Type:	Modified epoxy ester resin.
Propellant Type:	Dimethyl ether and carbon dioxide
Application Temperature:	5-30 °C

## Surface Preparation

All surfaces should be clean, dry and dust free before application.

Any surfaces covered in heavy grime/grease should be cleaned with SAFE STEP® Heavy Duty Cleaner, thoroughly washed down with water after use and allowed to dry.

### Steel Surfaces

These should be cleaned thoroughly before application. If possible, abrade the surface to provide an improved key for the paint.

### Concrete

The surface should be cleaned thoroughly before use. On new or smooth concrete treatment with an acid etch solution is recommended prior to application of EASYLINE®.

### Asphalt

Asphalt should be free from dust, dirt and grease etc. If necessary, the surface should be cleaned by pressure washing and allowing the asphalt to dry thoroughly before application of EASYLINE®.

## Before Application

Shake the can until the agitator balls start to rattle, then continue shaking for at least one minute to ensure the paint is homogeneous and there is no settlement.

Place on an actuator (nozzle) ensuring that all orifices are free of paint build up. If any orifice is blocked, discard the actuator. Do not try to remove paint with a pin or other such instrument, as this is likely to damage the actuator and it will not be possible to produce good quality lines.

## Application

EASYLINE EDGE aerosol paint has been designed to be used with the EASYLINE EDGE Applicator (Part Code 47010) or EASYLINE hand held applicator (Part Code 46013).

On new tarmac, paint a first line quickly to give only a light coverage. When this line has dried sufficiently (approximately one hour) re-apply Easyline® on top of the first line.

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E customer-service@rocol.com  
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

# Technical Data

**ROCOL®**

## Performance you can trust

### After Use

Always remove the can from the applicator. With the can in an upright position and pointing away from face, depress the actuator for 3-5 seconds to clear any paint residue.

Always store cans of EASYLINE® on their side securely in a cool place away from sources of ignition. Do not store in direct sunlight.

To clean the applicator discs, allow the paint to dry, then gently remove the paint with a paint scraper (due to the design of the disc system, this is easy).

### Removing Easyline® Paints

If for any reason you want to remove EASYLINE® paint (for example if a line has been painted in the wrong place) use a proprietary solvent based paint stripper and follow the directions on the can. On porous surfaces more than one application of paint stripper may be required.

### Warning

EASYLINE® is a pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not spray onto naked flame or any incandescent material. Do not pierce or burn after use.

### Health & Safety

Refer to Safety Data Sheet before use.

**Safety Data Sheets** – Safety data sheets are available for download from our website [www.rocol.com](http://www.rocol.com) or may be obtained from your usual ROCOL® contact.

**Disclaimer:** The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which may affect the use and performance of our products, for this reason it is given without responsibility.

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE